



Juniper Networks Secure Access

Client-Side Changes Guide

Release 6.4

Juniper Networks, Inc.
1194 North Mathilda Avenue
Sunnyvale, CA 94089
USA
408-745-2000
www.juniper.net

This product includes the Envoy SNMP Engine, developed by Epilogue Technology, an Integrated Systems Company. Copyright © 1986–1997, Epilogue Technology Corporation. All rights reserved. This program and its documentation were developed at private expense, and no part of them is in the public domain.

This product includes memory allocation software developed by Mark Moraes, copyright © 1988, 1989, 1993, University of Toronto.

This product includes FreeBSD software developed by the University of California, Berkeley, and its contributors. All of the documentation and software included in the 4.4BSD and 4.4BSD-Lite Releases is copyrighted by The Regents of the University of California. Copyright © 1979, 1980, 1983, 1986, 1988, 1989, 1991, 1992, 1993, 1994. The Regents of the University of California. All rights reserved.

GateD software copyright © 1995, The Regents of the University. All rights reserved. Gate Daemon was originated and developed through release 3.0 by Cornell University and its collaborators. Gated is based on Kirton's EGP, UC Berkeley's routing daemon (routed), and DCN's HELLO routing protocol. Development of Gated has been supported in part by the National Science Foundation. Portions of the GateD software copyright © 1988, Regents of the University of California. All rights reserved. Portions of the GateD software copyright © 1991, D. L. S. Associates.

Juniper Networks, the Juniper Networks logo, NetScreen, NetScreen Technologies, the NetScreen logo, NetScreen-Global Pro, ScreenOS, and GigaScreen are registered trademarks of Juniper Networks, Inc. in the United States and other countries.

The following are trademarks of Juniper Networks, Inc.: ERX, E-series, ESP, Instant Virtual Extranet, Internet Processor, J2300, J4300, J6300, J-Protect, J-series, J-Web, JUNOS, JUNOScope, JUNOScript, JUNOSe, M5, M7i, M10, M10i, M20, M40, M40e, M160, M320, M-series, MMD, NetScreen-5GT, NetScreen-5XP, NetScreen-5XT, NetScreen-25, NetScreen-50, NetScreen-204, NetScreen-208, NetScreen-500, NetScreen-5200, NetScreen-5400, NetScreen-IDP 10, NetScreen-IDP 100, NetScreen-IDP 500, NetScreen-Remote Security Client, NetScreen-Remote VPN Client, NetScreen-SA 1000 Series, NetScreen-SA 3000 Series, NetScreen-SA 5000 Series, NetScreen-SA Central Manager, NetScreen Secure Access, NetScreen-SM 3000, NetScreen-Security Manager, NMC-RX, SDX, Stateful Signature, T320, T640, T-series, and TX Matrix. All other trademarks, service marks, registered trademarks, or registered service marks are the property of their respective owners. All specifications are subject to change without notice.

Products made or sold by Juniper Networks or components thereof might be covered by one or more of the following patents that are owned by or licensed to Juniper Networks: U.S. Patent Nos. 5,473,599, 5,905,725, 5,909,440, 6,192,051, 6,333,650, 6,359,479, 6,406,312, 6,429,706, 6,459,579, 6,493,347, 6,538,518, 6,538,899, 6,552,918, 6,567,902, 6,578,186, and 6,590,785.

Copyright © 2009, Juniper Networks, Inc.
All rights reserved. Printed in USA.

Juniper Networks Secure Access Client-side Changes Guide, Release 6.4

Juniper Networks assumes no responsibility for any inaccuracies in this document. Juniper Networks reserves the right to change, modify, transfer, or otherwise revise this publication without notice.

Year 2000 Notice

Juniper Networks hardware and software products are Year 2000 compliant. The JUNOS software has no known time-related limitations through the year 2038. However, the NTP application is known to have some difficulty in the year 2036.

Software License

The terms and conditions for using this software are described in the software license contained in the acknowledgment to your purchase order or, to the extent applicable, to any reseller agreement or end-user purchase agreement executed between you and Juniper Networks. By using this software, you indicate that you understand and agree to be bound by those terms and conditions.

Generally speaking, the software license restricts the manner in which you are permitted to use the software and may contain prohibitions against certain uses. The software license may state conditions under which the license is automatically terminated. You should consult the license for further details.

For complete product documentation, please see the Juniper Networks Web site at www.juniper.net/techpubs.

End User License Agreement

READ THIS END USER LICENSE AGREEMENT ("AGREEMENT") BEFORE DOWNLOADING, INSTALLING, OR USING THE SOFTWARE. BY DOWNLOADING, INSTALLING, OR USING THE SOFTWARE OR OTHERWISE EXPRESSING YOUR AGREEMENT TO THE TERMS CONTAINED HEREIN, YOU (AS CUSTOMER OR IF YOU ARE NOT THE CUSTOMER, AS A REPRESENTATIVE/AGENT AUTHORIZED TO BIND THE CUSTOMER) CONSENT TO BE BOUND BY THIS AGREEMENT. IF YOU DO NOT OR CANNOT AGREE TO THE TERMS CONTAINED HEREIN, THEN (A) DO NOT DOWNLOAD, INSTALL, OR USE THE SOFTWARE, AND (B) YOU MAY CONTACT JUNIPER NETWORKS REGARDING LICENSE TERMS.

1. The Parties. The parties to this Agreement are Juniper Networks, Inc. and its subsidiaries (collectively "Juniper"), and the person or organization that originally purchased from Juniper or an authorized Juniper reseller the applicable license(s) for use of the Software ("Customer") (collectively, the "Parties").

2. The Software. In this Agreement, "Software" means the program modules and features of the Juniper or Juniper-supplied software, and updates and releases of such software, for which Customer has paid the applicable license or support fees to Juniper or an authorized Juniper reseller.

3. License Grant. Subject to payment of the applicable fees and the limitations and restrictions set forth herein, Juniper grants to Customer a non-exclusive and non-transferable license, without right to sublicense, to use the Software, in executable form only, subject to the following use restrictions:

- a. Customer shall use the Software solely as embedded in, and for execution on, Juniper equipment originally purchased by Customer from Juniper or an authorized Juniper reseller, unless the applicable Juniper documentation expressly permits installation on non-Juniper equipment.
- b. Customer shall use the Software on a single hardware chassis having a single processing unit, or as many chassis or processing units for which Customer has paid the applicable license fees.
- c. Product purchase documents, paper or electronic user documentation, and/or the particular licenses purchased by Customer may specify limits to Customer's use of the Software. Such limits may restrict use to a maximum number of seats, registered endpoints, concurrent users, sessions, calls, connections, subscribers, clusters, nodes, or transactions, or require the purchase of separate licenses to use particular features, functionalities, services, applications, operations, or capabilities, or provide throughput, performance, configuration, bandwidth, interface, processing, temporal, or geographical limits. Customer's use of the Software shall be subject to all such limitations and purchase of all applicable licenses.

The foregoing license is not transferable or assignable by Customer. No license is granted herein to any user who did not originally purchase the applicable license(s) for the Software from Juniper or an authorized Juniper reseller.

4. Use Prohibitions. Notwithstanding the foregoing, the license provided herein does not permit the Customer to, and Customer agrees not to and shall not: (a) modify, unbundle, reverse engineer, or create derivative works based on the Software; (b) make unauthorized copies of the Software (except as necessary for backup purposes); (c) rent, sell, transfer, or grant any rights in and to any copy of the Software, in any form, to any third party; (d) remove any proprietary notices, labels, or marks on or in any copy of the Software or any product in which the Software is embedded; (e) distribute any copy of the Software to any third party, including as may be embedded in Juniper equipment sold in the secondhand market; (f) use any 'locked' or key-restricted feature, function, service, application, operation, or capability without first purchasing the applicable license(s) and obtaining a valid key from Juniper, even if such feature, function, service, application, operation, or capability is enabled without a key; (g) distribute any key for the Software provided by Juniper to any third party; (h) use the Software in any manner that extends or is broader than the uses purchased by Customer from Juniper or an authorized Juniper reseller; (i) use the Software on non-Juniper equipment where the Juniper documentation does not expressly permit installation on non-Juniper equipment; (j) use the Software (or make it available for use) on Juniper equipment that the Customer did not originally purchase from Juniper or an authorized Juniper reseller; or (k) use the Software in any manner other than as expressly provided herein.

5. Audit. Customer shall maintain accurate records as necessary to verify compliance with this Agreement. Upon request by Juniper, Customer shall furnish such records to Juniper and certify its compliance with this Agreement.

6. Confidentiality. The Parties agree that aspects of the Software and associated documentation are the confidential property of Juniper. As such, Customer shall exercise all reasonable commercial efforts to maintain the Software and associated documentation in confidence, which at a minimum includes restricting access to the Software to Customer employees and contractors having a need to use the Software for Customer's internal business purposes.

7. Ownership. Juniper and Juniper's licensors, respectively, retain ownership of all right, title, and interest (including copyright) in and to the Software, associated documentation, and all copies of the Software. Nothing in this Agreement constitutes a transfer or conveyance of any right, title, or interest in the Software or associated documentation, or a sale of the Software, associated documentation, or copies of the Software.

8. Warranty, Limitation of Liability, Disclaimer of Warranty. The warranty applicable to the Software shall be as set forth in the warranty statement that accompanies the Software (the "Warranty Statement"). Nothing in this Agreement shall give rise to any obligation to support the Software. Support services may be purchased separately. Any such support shall be governed by a separate, written support services agreement. TO THE MAXIMUM EXTENT PERMITTED BY LAW, JUNIPER SHALL NOT BE LIABLE FOR ANY LOST PROFITS, LOSS OF DATA, OR COSTS OR PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES, OR FOR ANY SPECIAL, INDIRECT, OR CONSEQUENTIAL DAMAGES ARISING OUT OF THIS AGREEMENT, THE SOFTWARE, OR ANY JUNIPER OR JUNIPER-SUPPLIED SOFTWARE. IN NO EVENT SHALL JUNIPER BE LIABLE FOR DAMAGES ARISING FROM UNAUTHORIZED OR IMPROPER USE OF ANY JUNIPER OR JUNIPER-SUPPLIED SOFTWARE. EXCEPT AS EXPRESSLY PROVIDED IN THE WARRANTY STATEMENT TO THE EXTENT PERMITTED BY LAW, JUNIPER DISCLAIMS ANY AND ALL WARRANTIES IN AND TO THE SOFTWARE (WHETHER EXPRESS, IMPLIED, STATUTORY, OR OTHERWISE), INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NONINFRINGEMENT. IN NO EVENT DOES JUNIPER WARRANT THAT THE SOFTWARE, OR ANY EQUIPMENT OR NETWORK RUNNING THE SOFTWARE, WILL OPERATE WITHOUT ERROR OR INTERRUPTION, OR WILL BE FREE OF VULNERABILITY TO INTRUSION OR ATTACK. In no event shall Juniper's or its suppliers' or licensors' liability to Customer, whether in contract, tort (including negligence), breach of warranty, or otherwise, exceed the price paid by Customer for the Software that gave rise to the claim, or if the Software is embedded in another Juniper product, the price paid by Customer for such other product. Customer acknowledges and agrees that Juniper has set its prices and entered into this Agreement in reliance upon the disclaimers of warranty and the limitations of liability set forth herein, that the same reflect an allocation of risk between the Parties (including the risk that a contract remedy may fail of its essential purpose and cause consequential loss), and that the same form an essential basis of the bargain between the Parties.

9. Termination. Any breach of this Agreement or failure by Customer to pay any applicable fees due shall result in automatic termination of the license granted herein. Upon such termination, Customer shall destroy or return to Juniper all copies of the Software and related documentation in Customer's possession or control.

10. Taxes. All license fees for the Software are exclusive of taxes, withholdings, duties, or levies (collectively "Taxes"). Customer shall be responsible for paying Taxes arising from the purchase of the license, or importation or use of the Software.

11. Export. Customer agrees to comply with all applicable export laws and restrictions and regulations of any United States and any applicable foreign agency or authority, and not to export or re-export the Software or any direct product thereof in violation of any such restrictions, laws or regulations, or without all necessary approvals. Customer shall be liable for any such violations. The version of the Software supplied to Customer may contain encryption or other capabilities restricting Customer's ability to export the Software without an export license.

12. Commercial Computer Software. The Software is "commercial computer software" and is provided with restricted rights. Use, duplication, or disclosure by the United States government is subject to restrictions set forth in this Agreement and as provided in DFARS 227.7201 through 227.7202-4, FAR 12.212, FAR 27.405(b)(2), FAR 52.227-19, or FAR 52.227-14(ALT III) as applicable.

13. Interface Information. To the extent required by applicable law, and at Customer's written request, Juniper shall provide Customer with the interface information needed to achieve interoperability between the Software and another independently created program, on payment of applicable fee, if any. Customer shall observe strict obligations of confidentiality with respect to such information and shall use such information in compliance with any applicable terms and conditions upon which Juniper makes such information available.

14. Third Party Software. Any licensor of Juniper whose software is embedded in the Software and any supplier of Juniper whose products or technology are embedded in (or services are accessed by) the Software shall be a third party beneficiary with respect to this Agreement, and such licensor or vendor shall have the right to enforce this Agreement in its own name as if it were Juniper. In addition, certain third party software may be provided with the Software and is subject to the accompanying license(s), if any, of its respective owner(s). To the extent portions of the Software are distributed under and subject to open source licenses obligating Juniper to make the source code for such portions publicly available (such as the GNU General Public License ("GPL") or the GNU Library General Public License ("LGPL")), Juniper will make such source code portions (including Juniper modifications, as appropriate) available upon request for a period of up to three years from the date of distribution. Such request can be made in writing to Juniper Networks, Inc., 1194 N. Mathilda Ave., Sunnyvale, CA 94089, ATTN: General Counsel. You may obtain a copy of the GPL at <http://www.gnu.org/licenses/gpl.html>, and a copy of the LGPL at <http://www.gnu.org/licenses/lgpl.html>.

15. Miscellaneous. This Agreement shall be governed by the laws of the State of California without reference to its conflicts of laws principles. The provisions of the U.N. Convention for the International Sale of Goods shall not apply to this Agreement. For any disputes arising under this Agreement, the Parties hereby consent to the personal and exclusive jurisdiction of, and venue in, the state and federal courts within Santa Clara County, California. This Agreement constitutes the entire and sole agreement between Juniper and the Customer with respect to the Software, and supersedes all prior and contemporaneous agreements relating to the Software, whether oral or written (including any inconsistent terms contained in a purchase order), except that the terms of a separate written agreement executed by an authorized Juniper representative and Customer shall govern to the extent such terms are inconsistent or conflict with terms contained herein. No modification to this Agreement nor any waiver of any rights hereunder shall be effective unless expressly assented to in writing by the party to be charged. If any portion of this Agreement is held invalid, the Parties agree that such invalidity shall not affect the validity of the remainder of this Agreement. This Agreement and associated documentation has been written in the English language, and the Parties agree that the English version will govern. (For Canada: Les parties aux présentés confirment leur volonté que cette convention de même que tous les documents y compris tout avis qui s'y rattache, soient rédigés en langue anglaise. (Translation: The parties confirm that this Agreement and all related documentation is and will be in the English language)).

Table of Contents

Environmental Variable Definitions	1
Juniper Networks Installer Service.....	2
Installer Package File and File Location	2
Additional Package Files and File Locations	2
Files Remaining After Uninstall.....	3
Registry Modifications	3
Log File Location	3
Juniper Networks Setup.....	3
Installer Package Files	3
Additional Package Files and File Locations.....	3
Registry Modifications	5
Log File Location	5
Host Checker	6
Installer Package Files and File Location	6
Additional Installer Package Files and File Locations	6
Files Remaining After Uninstall	7
Registry Modifications.....	7
Log File Locations	8
Macintosh Clients	8
Application and Additional Files Installed by Host Checker	8
Files Remaining After Uninstall.....	8
Log files Installed by Host Checker.....	8
Linux Clients.....	9
Application and Additional Files Installed by Host Checker	9
Files Remaining After Uninstall.....	9
Log Files Installed by Host Checker	9
Secure Virtual Workspace	9
Registry Modifications	9
Files Remaining After Uninstall.....	9
Cache Cleaner	10
Installer Package File and File Locations.....	10
Additional Files Installed by Package and File Locations.....	10
Files Remaining After Uninstall.....	10
Registry Modifications	11
Log File Location	11
Secure Meeting	11
Installer Package File and File Location	11
Additional Files Installed by Package and File Locations	11
Files Remaining After Uninstall.....	12
Registry modifications	12
Log file locations.....	12
Macintosh Clients	13
Application and Additional Files Installed by Secure Meeting	13
Files Remaining After Uninstall	13

- Log files Installed by Secure Meeting..... 13
- Linux Clients..... 13
 - Application and Additional Files Installed by Secure Meeting..... 13
 - Log files Installed by Secure Meeting..... 13
- Secure Meeting Plug-In..... 14
 - File Location 14
 - Files remaining after uninstall 14
 - Registry modifications 14
- Windows Secure Application Manager (WSAM)..... 14
 - Installer Package Files and File Locations 14
 - Additional Files Installed by Package and File Locations 15
 - Files Remaining After Uninstall..... 16
 - Registry Modifications 17
 - Installation Values 17
 - Uninstallation Values..... 18
 - Current Version Values..... 18
 - TDI driver values (Windows 2000/XP/Vista only) 19
 - Miscellaneous..... 19
 - Log file location 19
- Java Secure Application Manager (JSAM) 20
 - Windows clients 20
 - Additional Files Installed by Package and File Locations 20
 - Files Remaining After Uninstall 20
 - Registry modifications 21
 - Log file locations 21
 - Macintosh Clients 21
 - Application and Additional Files Installed by JSAM..... 21
 - Files Remaining After Uninstall 22
 - Log files Installed by JSAM 22
 - Linux Clients..... 22
 - Application and Additional Files Installed by JSAM..... 22
 - Files Remaining After Uninstall 22
 - Log Files Installed by JSAM..... 22
- Network Connect and GINA 22
 - Windows Clients..... 22
 - Installer Package Files and File Locations..... 22
 - Hosts File Change 22
 - Additional Files Installed by Package and File Locations 23
 - Files Remaining After Uninstall 24
 - Registry Modifications..... 24
 - Log file Location..... 25
 - Linux Clients..... 25
 - Application and Additional Files Installed by Network Connect..... 25
 - Files Remaining After Uninstall 25
 - Log Files Installed by Network Connect..... 25
 - Macintosh Clients 26
 - Application and Additional Files Installed by Network Connect..... 26
 - Files Remaining After Uninstall 26
 - Log Files Installed by Network Connect..... 27
- Juniper Terminal Services Client 27
 - Installer Package Files and File Locations 27
 - Additional Files Installed by Package and File Locations 27
 - Files Remaining After Uninstall..... 28
 - Registry Modifications 28

Log File Location	29
Juniper Citrix Services Client	29
Installer Package Files and File Locations	29
Additional Files Installed by Package and File Locations	29
Files Remaining After Uninstall.....	30
Registry Modifications	30
Log File Location	31
Required rights to run and install applications	31

Client-Side Application Changes Guide

This guide lists the names of the package files used by the IVE to install client-side components, the names of the files the packages install and uninstall, and the registry changes the files make to the user's system. It also describes the permissions that are required to install and run various Instant Virtual Network (IVE) client-side components.

- “Environmental Variable Definitions” on page 1
- “Juniper Networks Installer Service” on page 2
- “Juniper Networks Setup” on page 3
- “Host Checker” on page 6
- “Secure Virtual Workspace” on page 9
- “Cache Cleaner” on page 10
- “Secure Meeting” on page 11
- “Windows Secure Application Manager (WSAM)” on page 14
- “Java Secure Application Manager (JSAM)” on page 20
- “Network Connect and GINA” on page 22
- “Juniper Terminal Services Client” on page 27
- “Juniper Citrix Services Client” on page 29

Environmental Variable Definitions

Environment variables are used throughout this guide. The environment variable definitions are as follows.

For Windows 2000 and Windows XP:

- %USERPROFILE% =%SystemDrive%\Documents and Settings\%USERNAME%
- %ALLUSERSPROFILE%=%SystemDrive%\Documents and Settings\All User
- %APPDATA% =%USERPROFILE%\Application Data

- %TEMP% =%USERPROFILE%\Local Settings\Temp

For Windows Vista:

- %USERPROFILE% =%SystemDrive%\Users\%USERNAME%
- %APPDATA% =%USERPROFILE%\AppData\Roaming

For low medium/high integrity processes:

- %TEMP% =%USERPROFILE%\AppData\Local\Temp

For low integrity processes:

- %TEMP% =%USERPROFILE%\AppData\Local\Temp\low

Juniper Networks Installer Service

When installing a Windows-based IVE client application on a user’s Windows system, the Juniper Installer Service deploys two files on the client machine:

- JuniperSetupSP1Control.ocx
- AccessServiceComponent.exe (The IVE auto-starts this service when installing, and , then stops and removes it when uninstalling.)

Installer Package File and File Location

The IVE loads the installer service files in the following locations:

- C:\Program files\Juniper Networks\Installer Service\AccessServiceComponent.exe (Windows NT/2000/XP)
- C:\WINNT\Downloaded Program Files\JuniperSetupSP1Control.ocx (Windows NT and 2000)
- C:\Windows\Downloaded Program Files\JuniperSetupSP1Control.ocx (Windows XP)

Additional Package Files and File Locations

The Juniper Installer Service installs the following files:



NOTE: For Windows NT and Windows 2000, the files are installed in C:\WINNT\Downloaded Program Files. For Windows XP and Windows Vista, the files are installed in C:\Windows\Downloaded Program Files.

File	Windows NT/2000	Windows XP/Vista
string_de.properties	X	X
string_en.properties	X	X
string_es.properties	X	X

File	Windows NT/2000	Windows XP/Vista
string_fr.properties	X	X
string_ja.properties	X	X
string_ko.properties	X	X
string_zh.properties	X	X
string_zh_cn.properties	X	X

Files Remaining After Uninstall

When the ActiveX control is deleted from within Internet Explorer, it leaves the following files behind:

- C:\Documents and Settings\\Application Data\Juniper Networks\Setup\JuniperSetupCtl.log
- C:\Program Files\Juniper Networks\Installer Service\NeoterisSetupService.log

Registry Modifications

The installer package creates a registry key under HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\Neoteris Setup Service

Log File Location

The Juniper Networks Installer Service installs the log files in the following location: C:\Program Files\Juniper Networks\Installer Service

Juniper Networks Setup

When a Windows user signs in to the IVE, the IVE attempts to install an ActiveX control (Juniper Networks Setup) on the user's system. If the IVE successfully installs Juniper Networks Setup, then the Juniper Networks Setup manages the installation of Windows-based IVE client applications.

Installer Package Files

The IVE loads the following installer files.

- JuniperSetupClient.ocx (Windows Vista/XP/2000)
- JuniperSetupClientInstaller.exe (Windows XP/2000)

Additional Package Files and File Locations

The Juniper Networks Setup installs the following additional files:



NOTE: For Windows XP and Windows 2000, the files are installed in C:\Documents and Settings\username\Application Data\Juniper Networks\Setup. For Windows Vista, the files are installed in C:\Users\username\AppData\Roaming\Juniper Networks\Setup Client.

File	Windows XP/2000	Windows Vista
dsmmf.exe	X	
dsmmfres_de.dll	X	
dsmmfres_es.dll	X	
dsmmfres_fr.dll	X	
dsmmfres_ja.dll	X	
dsmmfres_ko.dll	X	
dsmmfres_zh.dll	X	
dsmmfres_zh_cn.dll	X	
JuniperSetupApp.exe	X	
JuniperSetupClient.exe		X
JuniperSetupClient.ini		X
JuniperSetupClientOCX.exe		X
JuniperSetupCtrl.log	X	
JuniperSetupDLL.dll	X	
JuniperSetupDLL.log	X	
JuniperSetupOCX.exe		X
NeoterisSetup.ocx	X	
setupResource_de.dll	X	
setupResource_en.dll	X	
setupResource_es.dll	X	
setupResource_fr.dll	X	
setupResource_ja.dll	X	
setupResource_ko.dll	X	
setupResource_zh.dll	X	
setupResource_zh_cn.dll	X	
string_de.properties	X	
string_en.properties	X	
string_es.properties	X	
string_fr.properties	X	
string_ja.properties	X	
string_ko.properties	X	
string_zh.properties	X	
string_zh_cn.properties	X	
uninstall.exe	X	
uninstallOCX.exe		X
versionInfo.ini	X	

Registry Modifications

For Windows Vista, the Juniper Networks Setup creates the following registry keys in HKEY_CURRENT_USER\SOFTWARE\Microsoft\Internet Explorer\Low Rights\ElevationPolicy\{3E8944DC-79B5-4650-9C2E-83885548A119}:

String	Set to
AppName	"JuniperSetupClient.exe."
AppPath	"\$OUTDIR"
Policy	"3"

Additionally, the Juniper Setup creates the following registry keys in HKEY_CURRENT_USER\SOFTWARE\Microsoft\Windows\CurrentVersion\Uninstall\\${NEO_FULL_NAME}:

String	Set to
DisplayName	"\${NEO_COMPANY_NAME} \${NEO_DISPLAY_NAME}"
UninstallString	"\$INSTDIR\uninstall.exe"
StartupApp	"\$INSTDIR\JuniperSetupClient.exe"
StopApp	"\$INSTDIR\JuniperSetupClient.exe -stop"
DisplayVersion	"\$NEO_SETUP_CLIENT_VERSION}"
Publisher	"\${NEO_COMPANY_NAME}"
URLInfoAbout	"http://www.juniper.net"

Log File Location

The Juniper Networks Setup installs the log files in the following locations.

For Windows XP and Windows 2000:

- C:\Documents and Settings\All Users\Application Data\Juniper Networks\Logging\debuglog.log
- C:\Documents and Settings\\Application Data\Juniper Networks\Setup\JuniperSetupControlXPlog (ActiveX logs)

For Windows Vista:

- C:\Users\username\AppData\Roaming\Juniper Networks\Logging\debuglog.log
- C:\Users\username\AppData\Local\Temp\Low\JuniperSetupClientControl.log (for ActiveX logs)

For low-integrity processes, such as Internet Explorer 7, the ActiveX installer installs the following log files in C:\Users\username\AppData\Local\Temp\Low:

- JuniperSetupClientCtrl.log
- JuniperSetupDll.log

Host Checker

To run Host Checker, the IVE downloads the `dsHostCheckerSetup.exe.cab` package to the user's client. This package is responsible for downloading additional files to the user's system in order to run Host Checker. Host Checker deletes the `dsHostCheckerSetup.exe.cab` package after installation is complete.

Installer Package Files and File Location

Host Checker installs the following CAB file: `%TEMP%\dsHostCheckerSetup.exe.cab`

Additional Installer Package Files and File Locations

Host Checker installs the following additional files on the client in `C:\Documents and Settings\username\Application Data\Juniper Networks\Host Checker`:

- `CertAuthIMC.dll`
- `dsHostChecker.exe`
- `dsHostCheckerProxy.exe`
- `dsHostCheckerResource_de.dll`
- `dsHostCheckerResource_en.dll`
- `dsHostCheckerResource_es.dll`
- `dsHostCheckerResource_fr.dll`
- `dsHostCheckerResource_ja.dll`
- `dsHostCheckerResource_ko.dll`
- `dsHostCheckerResource_zh.dll`
- `dsHostCheckerResource_zh_cn.dll`
- `dsnsisdll.dll`
- `dsWinClient.dll`
- `dsWinClientResource_DE.dll`
- `dsWinClientResource_EN.dll`
- `dsWinClientResource_ES.dll`
- `dsWinClientResource_FR.dll`
- `dsWinClientResource_JA.dll`
- `dsWinClientResource_KO.dll`
- `dsWinClientResource_ZH.dll`
- `dsWinClientResource_ZH_CN.dll`

- EPCheck.dll
- hcimc.dll
- install.log
- JSystemIMC.dll
- msvcp60.dll
- restore_win2k.txt
- restore_win98.txt
- ShavlikIMC.dll
- tnc_config
- uninstall.exe
- versionInfo.ini

In addition, if you implement policies that download or check for third-party software, Host Checker may install additional DLLs in subdirectories of: `C:\Documents and Settings\username\Application Data\Juniper Networks\Host Checker`.

For example, if you implement Advanced Endpoint Defense Malware Protection policies, Host Checker creates a subdirectory called `policy_x` in this directory and installs Whole Security DLLs in this folder.

Files Remaining After Uninstall

`jnprvamgr.sys`.

Registry Modifications

Host Checker sets the following registry values:

String	Set in
LogFile	HKEY_CURRENT_USER\SOFTWARE\Juniper Networks\Host Checker\Debug\dsHostChecker
level	HKEY_CURRENT_USER\SOFTWARE\Juniper Networks\Host Checker\Debug\dsHostChecker
Language	HKEY_CURRENT_USER\SOFTWARE\Juniper Networks\Host Checker
InstallPath	HKEY_CURRENT_USER\SOFTWARE\Juniper Networks\Host Checker

Additionally, Host Checker sets the following values in `HKEY_CURRENT_USER\Software\Microsoft\Windows\CurrentVersion\Uninstall\Neoteris_Host_Checker`:

String	Set to
DisplayName	“Juniper Networks Host Checker”
DisplayVersion	current product version number
Publisher	“Juniper Networks”
QuietUninstallString	"C:\Documents and Settings\ <i>username</i> \Application Data\Juniper Networks\Host Checker <version number>\uninstall.exe" /S"
StartupApp	“C:\Documents and Settings\ <i>username</i> \Application Data\Juniper Networks\Host Checker\dsHostChecker.exe”
StopApp	“C:\Documents and Settings\ <i>username</i> \Application Data\Juniper Networks\Host Checker\dsHostChecker.exe - stop”
UninstallString	“C:\Documents and Settings\ <i>username</i> \Application Data\Juniper Networks\Host Checker\uninstall.exe”
URLInfoAbout	“http://www.juniper.net”

Log File Locations

You can enable or disable client-side logs through the **System > Log/Monitoring > Client Logs > Settings** tab of the Web console.

When you enable logging, Host Checker adds log files to the following locations:

- C:\Documents and Settings\All Users\Application Data\Juniper Networks\Logging\debuglog.log (Windows XP)
- C:\users*username*\AppData\Roaming\Juniper Networks\Logging\debuglog.log (Windows Vista)
- C:\Users\Public\Juniper Networks\Logging\debuglog.log (Windows Vista)

Macintosh Clients

The following information applies to Macintosh clients only.

Application and Additional Files Installed by Host Checker

Host Checker installs the following files on the Macintosh client:

- ~/Library/Application Support/Juniper Networks/tncc.jar
- ~/Library/Application Support/Juniper Networks/hcport.txt

Files Remaining After Uninstall

There is no Host Checker uninstall on the Macintosh client.

Log files Installed by Host Checker

Host Checker stores the log files in the following location on the Macintosh client:
~/Library/Logs/Juniper Networks.

Linux Clients

The following information applies to Linux clients only.

Application and Additional Files Installed by Host Checker

Host Checker installs `$HOME/.juniper_networks/tbcc.jar` on the Linux client.

Files Remaining After Uninstall

The following files remain on the Linux client after uninstall:

- `$HOME/.juniper_networks/dsHCLauncher_linux1.log`
- `$HOME/.juniper_networks/dsHostChecker_linux1.log`

Log Files Installed by Host Checker

Host Checker installs the following log files on Linux systems.

- `$HOME/.juniper_networks/dsHCLauncher_linux1.log`
- `$HOME/.juniper_networks/dsHostChecker_linux1.log`

Secure Virtual Workspace

To run Secure Virtual Workspace (SVW), Host Checker downloads `neoSVWData.zip` and `neoSVWDlls.zip`. Then Host Checker unzips the following files onto the client computer under `C:\Documents and Settings\username\Application Data\Juniper Networks\Host Checker\policy_number`:

- `wallpaper.bmp`
- `dsjvd.dll`
- `dsjvdsvc.dll`
- `dsmonitor.dll`
- `dsVdeskPackage.dll`

Host Checker deletes `neoSVWData.zip` and `neoSVWDlls.zip` after unzipping the files.

Registry Modifications

SVW creates the key `HKEY_CURRENT_USER\SOFTWARE\Juniper Networks\VDesk`.

Files Remaining After Uninstall

None. Host Checker uninstalls SVW as part of the Host Checker uninstallation process.

Cache Cleaner

To run Cache Cleaner, the IVE downloads `neoCacheCleanerSetup.exe` to the user's Windows client. This package is responsible for downloading additional files to the user's system to execute Cache Cleaner.

Installer Package File and File Locations

Cache Cleaner installs the `Setup.exe` file on the Windows client in `%TEMP%\neoCacheCleanerSetup.exe`.

This file is removed once the installation is complete.

Additional Files Installed by Package and File Locations

Cache Cleaner installs the following additional files on the client in `%APPDATA%\Juniper Networks\Cache Cleaner version_number`:

- `dsCacheCleaner.exe`
- `uninstall.exe`
- `versionInfo.ini`
- `dsWinClientResource_DE.dll`
- `dsWinClientResource_EN.dll`
- `dsWinClientResource_ES.dll`
- `dsWinClientResource_FR.dll`
- `dsWinClientResource_JA.dll`
- `dsWinClientResource_KO.dll`
- `dsWinClientResource_ZH.dll`
- `dsWinClientResource_ZH_CN.dll`

Cache Cleaner also installs the following files on the client in `%APPDATA%\Juniper Networks\Cache Cleaner version number\Microsoft.VC80.CRT`:

- `Microsoft.VC80.CRT.manifest`
- `msvcr80.dll`

Files Remaining After Uninstall

None.

Registry Modifications

Cache Cleaner sets the following string registry values in HKEY_CURRENT_USER\Software\Microsoft\Windows\CurrentVersion\Uninstall\Juniper_Networks_Cache_Cleaner <version number>:

String	Set to
DisplayName	“Juniper Networks Cache Cleaner <version>”
DisplayVersion	the current software version
Publisher	“Juniper Networks”
QuietUninstallString	“%APPDATA%\Juniper Networks\Cache Cleaner <version number>\uninstall.exe /S”
StartupApp	“%APPDATA%\Juniper Networks\Cache Cleaner<version number>\dsCacheCleaner.exe”
StopApp	“%APPDATA%\Juniper Networks\Cache Cleaner<version number>\dsCacheCleaner.exe” -action stop -nodelete 1”
UninstallString	“%APPDATA%\Juniper Networks\Cache Cleaner<version number>\uninstall.exe”
URLInfoAbout	“http://www.juniper.net”

Log File Location

You can enable or disable client-side logs by clicking **System > Log/Monitoring > Client Logs > Settings** in the Web console. For Windows 2000 and Windows XP, when you enable logging Cache Cleaner adds log files to %ALLUSERSPROFILE%\Application Data\Juniper Networks\Logging\debuglog.log.

For Windows Vista, Cache Cleaner adds log files to %APPDATA%\Juniper Networks\Logging\debuglog.log.

Secure Meeting

To execute the Windows version of Secure Meeting, the IVE downloads the neoCBoxSetup.exe.cab package to the user’s computer.

Installer Package File and File Location

Secure Meeting installs the neoCBoxSetup.exe.cab file on the Windows client in C:\Documents and Settings\username\Local Settings\Temp\neoCBoxSetup.exe.cab

Additional Files Installed by Package and File Locations

With an Active-X based install, Secure Meeting installs additional files in:

- (Windows NT/2000/XP) C:\Documents and Settings\username\Application Data\Juniper Networks\Secure Meeting *version_number*
- (Windows Vista) C:\Program Files\Juniper Networks\Secure Meeting *version_number*

See the Secure Meeting directory for a complete list of files.

Files Remaining After Uninstall

After Secure Meeting uninstalls, the `cbox_cfg.ini` and `cbox_cfg.txt` files (for the Java client) remain on the client.

Registry modifications

Secure Meeting sets the following registry values:

String	Set in
Language	HKEY_CURRENT_USER\Software\Juniper Networks\Secure Meeting <version number>
level	HKLM\Software\Juniper Networks\Logging\Level

Log file locations

You can enable or disable client-side logs by clicking **System > Log/Monitoring > Client Logs > Settings** in the Web console.



NOTE: The maximum file size for each of the Secure Meeting log files is 10 MB.

When you enable logging, Secure Meeting adds log files to the following locations for Windows XP:

- C:\Documents and Settings\All Users\Application Data\Juniper Networks\Logging\debuglog.log
- C:\Documents and Settings\username\Application Data\Juniper Networks\Logging\debuglog.log
- C:\Documents and Settings\username\Application Data\Juniper Networks\Secure Meeting <version number>\SecureMeetingOutlook.log -and- SecureMeetingOutlook.log.old
- C:\Documents and Settings\username\Application Data\Juniper Networks\Secure Meeting <version number>\SecureMeetingOutlookApp.log -and- SecureMeetingOutlookApp.log.old

When you enable logging, Secure Meeting adds log files to the following locations for Windows Vista:

- C:\Users\Public\Juniper Networks\Logging\debuglog.log
- C:\Users\username\AppData\Roaming\Juniper Networks\Logging\debuglog.log
- C:\Users\username\AppData\Roaming\Juniper Networks\Secure Meeting <version number>\SecureMeetingOutlook.log -and- SecureMeetingOutlook.log.old
- C:\Users\username\AppData\Roaming\Juniper Networks\Secure Meeting <version number>\SecureMeetingOutlookApp.log -and- SecureMeetingOutlookApp.log.old

Macintosh Clients

The following information applies to Macintosh clients only.

Application and Additional Files Installed by Secure Meeting

Secure Meeting installs the following files on the Macintosh client:

- ~/Library/Application Support/Juniper Networks/meetingAppMac.jar
- ~/Library/Application Support/Juniper Networks/cbox_cnfg.txt
- ~/Library/Application Support/Juniper Networks/meeting.icns

Files Remaining After Uninstall

There is no Secure Meeting uninstall on the Macintosh client.

Log files Installed by Secure Meeting

Secure Meeting installs log files in the following locations on the Macintosh client:

- ~/Library/Logs/Juniper Networks/dsCboxLauncher_mac<x>.log, where <x> is 0 or 1
- ~/Library/Logs/Juniper Networks/dsCboxUI_mac<x>.log, where <x> is 0 or 1
- ~/Library/Logs/Juniper Networks/dsCboxUISummary_mac<x>.log, where <x> is 0 or 1
- ~/Library/Logs/Juniper Networks/MacPresenter.log

Linux Clients

The following information applies to Linux clients only.

Application and Additional Files Installed by Secure Meeting

Secure Meeting installs the following files on the Linux client:

- ~/.juniper_networks/meetingAppSun.jar
- ~/.juniper_networks/libSMJNIXWinLinux.so

Log files Installed by Secure Meeting

Secure Meeting installs log files in the following locations on the Linux client:

- ~/.juniper_networks/LinuxPresenter<x>.log where <x> is 0 or 1
- ~/.juniper_networks/dsCboxUISummary_linux<x>.log where <x> is 0 or 1
- ~/.juniper_networks/dsCboxUI_linux<x>.log where <x> is 0 or 1
- ~/.juniper_networks/dsCboxLauncher_linux<x>.log where <x> is 0 or 1

Secure Meeting Plug-In

To run the Secure Meeting plug-in, the IVE downloads the Secure Meeting Outlook plug-in to the user's client.

File Location

The Secure Meeting plug-in is installed on the Windows client in \Documents and Settings\\Application Data\Juniper Networks\Secure Meeting Outlook Plugin

Files remaining after uninstall

After the Secure meeting plug-in is uninstalled, the SecureMeetingOutlook.log file remains on the client.

Registry modifications

String	Set in
Language	HKEY_CURRENT_USER\Juniper Networks\Secure Meeting Outlook Plugin

Windows Secure Application Manager (WSAM)

To run WSAM, the IVE downloads `samsetup.exe` or `samsetupnt.exe` to the user's client, depending on the user's platform. These packages are responsible for downloading additional files to the user's system to run WSAM.

Installer Package Files and File Locations

WSAM downloads its package files to the following locations:

- Windows 2000 and Windows XP:
C:\Documents and Settings\username\Local Settings\Temp\samsetupnt.exe
- Windows Mobile 6.0 Pocket PC/6.0 Classic/6.0 Professional:
\My Documents\WSAMInstARM.cab
- Windows Mobile 5.0 SmartPhone/6.0 Standard:
\My Document\WSAMInstARMSPCab



NOTE: You may choose to use a WSAM standalone installer or scriptable installer instead of the standard Web installers already mentioned. If you do, the installers are located where you save them, which may not be the same directories listed here. The filenames for these downloadable installers are:

- WSAMInstNt.exe—WSAM standalone installer for Windows 2000/XP systems
 - WSAMInstARM.cab—WSAM standalone installer for Windows Mobile 5.0 PocketPC/6.0 Classic/6.0 Professional
 - WSAMInstARMSPcab—WSAM standalone installer for Windows Mobile 5.0 Smartphone/6.0 Standard
-

Additional Files Installed by Package and File Locations

For Windows XP or Windows Vista, WSAM installs the following additional files on the client in C:\Program Files\Juniper Networks\Secure Application Manager:

- dsSamProxy.exe
- dsSamResource_DE.dll
- dsSamResource_EN.dll
- dsSamResource_ES.dll
- dsSamResource_FR.dll
- dsSamResource_JA.dll
- dsSamResource_KO.dll
- dsSamResource_ZH.dll
- dsSamResource_ZH_CN.dll
- dsSamUI.exe
- dsWinClient.dll
- dsWinClientResource_DE.dll
- dsWinClientResource_EN.dll
- dsWinClientResource_ES.dll
- dsWinClientResource_FR.dll
- dsWinClientResource_JA.dll
- dsWinClientResource_KO.dll
- dsWinClientResource_ZH.dll
- dsWinClientResource_ZH_CN.dll
- gaptbar.dll

- install.log
- samclean.exe
- samdiagEx.dll (Windows 2000/XP/Vista only)
- samlauncher.exe
- SAMNB.dll (Windows 2000/XP/Vista only)
- UninstallSAM.exe
- versionInfo.ini

On Windows 2000, XP, or Vista systems, WSAM also installs a TDI driver (neofltr_<release number>_<build number>.sys) in \$SystemRoot\system32\drivers. (For example, for release 5.2.0.9300, WSAM installs NEOFLTR_520_9300.sys in C:\WINDOWS\System32\drivers\)

For Windows mobile, WSAM installs the following additional files on the client in \Program Files\Juniper Networks\WSAM:

File	Location
dsSamProxy.exe	\Program Files\Juniper Networks\WSAM
gapsp.dll	\Windows
SamResource_DE.dll	\Program Files\Juniper Networks\WSAM
SamResource_EN.dll	\Program Files\Juniper Networks\WSAM
SamResource_ES.dll	\Program Files\Juniper Networks\WSAM
SamResource_FR.dll	\Program Files\Juniper Networks\WSAM
SamResource_JA.dll	\Program Files\Juniper Networks\WSAM
SamResource_KO.dll	\Program Files\Juniper Networks\WSAM
SamResource_ZH.dll	\Program Files\Juniper Networks\WSAM
SamResource_ZH_CN.dll	\Program Files\Juniper Networks\WSAM
SamUI.exe	\Program Files\Juniper Networks\WSAM

Files Remaining After Uninstall

After WSAM uninstalls, the following files remain on the Windows 2000 or Windows XP client:

- samnsp.dll
- samclean.exe

Registry Modifications

WSAM sets the following registry values for the installation, uninstallation, current version, TDI driver for Windows 2000, XP, and Vista only, and miscellaneous:

Installation Values

For Windows XP or Windows Vista, WSAM sets the following installation values in HKEY_LOCAL_MACHINE\SOFTWARE\Juniper Networks\Secure Application Manager:

String	Set to
InstallPath	C:\Program Files\Juniper Networks\Secure Application Manager
Language	EN (or appropriate language value)

For Windows Mobile, WSAM sets the following installation values:

- In HKEY_LOCAL_MACHINE\SOFTWARE\Juniper Networks\WSAM:

String	Set to
AutoStart	0 or 1
ProductVersion	<version number><build number>
ProductName	WSAM

- HKEY_LOCAL_MACHINE\SOFTWARE\Juniper Networks\WSAM\Config

String	Set to
Url1	???

- HKEY_LOCAL_MACHINE\SOFTWARE\Juniper Networks\WSAM\Log:

String	Set to
LoggingApps	iexplore.exe; tmail.exe
LogLevel	3
ProductLocation	\Program Files\Juniper Networks\WSAM

- HKEY_LOCAL_MACHINE\SOFTWARE\Juniper Networks\WSAM

String	Set to
EnableLogSvr	0 or 1 (depending upon server side log setting)

- HKEY_CURRENT_USER\SOFTWARE\Juniper Networks\WSAM

String	Set to
UpgradeFlag	2 or 3 (depending upon auto profile generation requirement)

Uninstallation Values

WSAM sets the following uninstall values in HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Windows\CurrentVersion\Uninstall\Netris_Secure_Application_Manager\Commands for Windows 2000, XP and Windows Vista.

String	Set to
EnableLogSvr	0 or 1, depending on server side log setting.

WSAM also sets the following locations:

- HKEY_CURRENT_USER\SOFTWARE\Juniper Networks\Secure Application Manager\ \SessionEstablishTasks
- HKEY_CURRENT_USER\SOFTWARE\Juniper Networks\Secure Application Manager\ \SessionCleanupTasks
- HKEY_CURRENT_USER\SOFTWARE\Juniper networks\Secure Application Manager.
- HKEY_CURRENT_USER\SOFTWARE\Juniper Networks\Secure Application Manager\SessionEstablishTasks
- HKEY_CURRENT_USER\SOFTWARE\Juniper Networks\Secure Application Manager\ SessionCleanupTasks

Current Version Values

WSAM sets the following uninstall and version information values in HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Windows\CurrentVersion\Uninstall\Netris_Secure_Application_Manager:

String	Set to
DisplayName	“Juniper Networks Secure Application Manager”
DisplayVersion	< version number > < build number >
Publisher	Juniper Networks
QuietUninstallString	C:\Program Files\Juniper Networks\Secure Application Manager\UninstallSAM.exe
StartupApp	C:\Program Files\Juniper Networks\Secure Application Manager\dsSamProxy.exe
UninstallString	C:\Program Files\Juniper Networks\Secure Application Manager\UninstallSAM.exe
URLInfoAbout	http://www.juniper.net/products/ssl

In addition, WSAM sets the following version values:

Location	Set
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Windows\CurrentVersion\Internet Settings\Zones\1	1A00 to: 1

Location	Set
HKEY_CURRENT_USER\SOFTWARE\Microsoft\Windows\CurrentVersion\Internet Settings\Zones\1	1A00 to: 1

TDI driver values (Windows 2000/XP/Vista only)

WSAM sets the following values for the TDI driver on Windows 2000 and Windows XP systems in

HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\NEOFLTR_releaseNumber_buildNumber:

String	Set to
DisplayName	Juniper Networks TDI Filter Driver (NEOFLTR_releaseNumber_buildNumber)
ImagePath	C:\WINDOWS\System32\Drivers\NEOFLTR_releaseNumber_buildNumber.SYS

WSAM sets the following values in

HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\NEOFLTR_releaseNumber_buildNumber\Enum:

Type	Name	Value
String	0	Root\LEGACY_NEOFLTR_releaseNumber_buildNumber\0000
DWord	Count	0x00000001
DWord	NextInstance	0x00000001

WSAM sets the following value in

HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\AFD\Parameters

String	Set to
IrpStackSize	Applicable TDI Irp stack size, if required

Miscellaneous

WSAM sets the following miscellaneous registry values:

- String: IntranetAuthOptions is set in HKEY_LOCAL_MACHINE\SOFTWARE\Neoteris\Secure Application Manager\Backup and HKEY_CURRENT_USER\SOFTWARE\Neoteris\Secure Application Manager\Backup.

Log file location

You can enable or disable client-side logs by clicking **System > Log/Monitoring > Client Logs > Settings** in the Web console. When you enable logging, WSAM adds log files to the following location:

For Windows 2000/XP:

- C:\Documents and Settings\All Users \Application Data\Juniper Networks\Secure Application Manager
- C:\Documents and Settings\All Users \Application Data\Juniper Networks\Logging

For Windows Vista:

- C:\Users\username\AppData\Juniper Networks\Secure Application Manager
- C:\Users\username\AppData \Juniper Networks\Logging.

WSAM also adds an installation log file to the C:\Program Files\Juniper Networks\Secure Application Manager directory.

For Windows Mobile 5 users, WSAM adds log files to the \Program Files\Juniper Networks\WSAM\Log directory.

Java Secure Application Manager (JSAM)

To run JSAM, the IVE launches an applet on the user's client. This applet handles downloading additional files to the user's system in order to run JSAM.

In addition, JSAM modifies the hosts file if you choose **Automatic host-mapping** under **Users > User Roles > Role > SAM > Options > Java SAM Options**.

Windows clients

Additional Files Installed by Package and File Locations

For Windows 2000/XP, JSAM installs additional files in: C:\Documents and Settings\username\Application Data\Juniper Networks\Java Secure Application Manager

For Windows Vista:

- If UAC is disabled, JSAM installs C:\Users\username\AppData\Roaming\Juniper Networks\jsamtool.exe.
- If UAC is enabled, JSAM installs C:\Users\username\AppData\Local\Temp\Low\Juniper Networks\Java Secure Application Manager\jsamtool.exe.

Files Remaining After Uninstall

For Windows 2000/XP, after JSAM uninstalls, only the log files remain on the client, as described in "Log file locations" on page 21.

For Windows Vista, after JSAM uninstalls, files in C:\Users\username\AppData\Local\Temp\Low\Juniper Networks\Java Secure Application Manager remain.

Registry modifications

JSAM sets the following registry values:

- If you configure a standard NetBIOS application through JSAM, or you configure a custom application on port 137, 138, or 139, JSAM makes the following registry key modification on Windows XP machines (Administrator privileges required): `SMBDeviceEnabled=dword:00000000` is set in the registry location: `HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\NetBT\Parameters`.
- If you enable Outlook 5.5, 2000, or 2002 (Administrator privileges required), JSAM adds `HKEY_LOCAL_MACHINE\Software\Microsoft\Exchange\Exchange Provider\Rpc_Binding_Order` to the registry. (The second entry for this registry key is changed to `ncacn_http`.)

The original value of this setting is:

```
ncalrpc,ncacn_ip_tcp,ncacn_spx,ncacn_np,netbios,ncacn_vns_spp
```

After JSAM is initially used, the value of this setting is:

```
ncalrpc,ncacn_http,ncacn_ip_tcp,ncacn_spx,ncacn_np,netbios,ncacn_vns_spp
```

- If you disable the Skip Web Proxy Registry Check option under Users > User Roles > Role > SAM > Options > Java SAM Options (User read access required), JSAM reads: `HKEY_CURRENT_USER\SOFTWARE\Microsoft\Windows\CurrentVersion\Internet Settings\ProxyEnable`

Log file locations

You can enable or disable client-side logs by clicking **System > Log/Monitoring > Client Logs > Settings** in the Web console.

For Windows 2000/XP, when you enable logging, JSAM adds `C:\Documents and Settings\username\Application Data\Juniper Networks\Java Secure Application Manager\dsJSAM_win0.log` and `dsJSAM_win1.log`

For Windows Vista, when you enable logging, JSAM adds `C:\Users\username\AppData\Local\Temp\Low\Juniper Networks\Java Secure Application Manager\jsamtool.log` and `dsJSAM_win1.log`.

Macintosh Clients

The following information applies to Macintosh clients only.

Application and Additional Files Installed by JSAM

JSAM installs the following files on the Macintosh client:

- `~/Library/Application Support/Juniper Networks/NeoterisMac.jar`
- `~/Library/Java/Extensions/libJNPRAuthKit.jnilib`
- `~/Library/Application Support/Juniper Networks/jsam.icns`
- `~/Library/Application Support/Juniper Networks/logo.gif`

Files Remaining After Uninstall

The following file remains on the Macintosh client after uninstall:
~/Library/Logs/Juniper Networks/Java Secure Application Manager

Log files Installed by JSAM

JSAM installs log files in the following location on the Macintosh client:
~/Library/Logs/Juniper Networks/Java Secure Application Manager

Linux Clients

The following information applies to Linux clients only.

Application and Additional Files Installed by JSAM

JSAM does not install any application files on the Linux client.

Files Remaining After Uninstall

The only files that remain on the Linux client after uninstall are the log files.

Log Files Installed by JSAM

JSAM adds log files to the ~/.juniper_networks directory.

Network Connect and GINA

Windows Clients

To run Network Connect and Graphical Identification and Authorization (GINA), the IVE downloads the NcSetup.exe.cab package to the user's Windows client. This package is responsible for downloading additional files to the user's system in order to run Network Connect and GINA.

Installer Package Files and File Locations

- C:\Documents and Settings\username\Local Settings\Temp\neoNCsetup.exe.cab (Windows 2000/XP)
- C:\Users\username\AppData\Local\Temp\neoNCSetup.exe (Windows Vista)

Hosts File Change

A hosts file entry is added by Network Connect to support the following case:

- If, when Network Connect connects, split tunneling is disabled and the original externally resolved hostname (the hostname the user initially connected to prior to the NC launch) resolves to another IP address against the internal DNS, the browser will redirect to a *Server not found* page, because no route is defined within the client system.
- At a graceful termination (sign-out or timeout) of the Network Connect client connection, the hosts file is restored. If the hosts file was not restored in a prior case due to an ungraceful termination, the hosts file will be restored the next time the user launches Network Connect.

Additional Files Installed by Package and File Locations

On Windows 2000, XP and Windows Vista, Network Connect installs the following additional files on the client in the following locations. The following files are installed in C:\Program Files\Juniper Networks\Network Connect *version_number*:

- dsNcAdmin.dll
- dsNetworkConnect.exe
- dsNcDiag.dll
- versionInfo.ini
- dsNcGina.dll
- dsNCGINACompatible.txt
- dsNCRResource_EN.dll
- dsNCRResource_DE.dll
- dsNCRResource_ES.dll
- dsNCRResource_FR.dll
- dsNCRResource_JA.dll
- dsNCRResource_KO.dll
- dsNCRResource_ZH.dll
- dsNCRResource_ZH_CN.dll
- dsWinClientResource_EN.dll
- dsWinClientResource_DE.dll
- dsWinClientResource_ES.dll
- dsWinClientResource_FR.dll
- dsWinClientResource_JA.dll
- dsWinClientResource_KO.dll
- dsWinClientResource_ZH.dll
- dsWinClientResource_ZH_CN.dll
- JuniperSetupClientOCX.exe
- JuniperSetupOCX.exe
- uninstall.exe
- nclauncher.exe
- setproxy.html

Network Connect also installs the following files:

- C:\Program Files\Juniper Networks\Common Files\dsNcService.exe
- C:\<WINDIR>\system32\drivers\dsNcAdpt.sys
- C:\<WINDIR>\system32\dsGinaLoader.dll (Windows 2000 and Windows XP)

For Windows Vista, Network Connect also installs the following files:

- %windows%\system32\dsNCCredProv.dll
- %windows%\system32\dsNcSmartCardProv.dll

Files Remaining After Uninstall

After Network Connect uninstalls, the following files remain on the client:

- dsGinaLoader.dll

If only one Network Connect installation is present on the client, this file is removed after you reboot. If there are multiple versions of Network Connect installed on the client, this file remains on the client.

- C:\Program Files\Juniper Networks\Common Files\Config.ini

Registry Modifications

Additionally, if GINA is enabled in the Admin Web console, Network Connect sets following string registry value in HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Winlogon (Windows 2000 and Windows XP only):

String	Set to
GinaDLL	"dsGinaLoader.dll"

Network Connect creates the following keys:

- HKEY_LOCAL_MACHINE\SOFTWARE\Juniper Networks\Network Connect < version number >
- HKEY_CURRENT_USER\Software\Juniper Networks\Network Connect < version number >
- (Windows Vista only) HKEY_LOCAL_MACHINE "SOFTWARE\Microsoft\Windows\CurrentVersion\Authentication\PLAP Providers\{9f4a51 de-92b1-483a-b717-dd7d3bb7d3db}"
- (Windows Vista only) HKEY_CLASSES_ROOT "CLSID\{9f4a51 de-92b1-483a-b717-dd7d3bb7d3db}"
- (Windows Vista only) HKEY_LOCAL_MACHINE "SOFTWARE\Microsoft\Windows\CurrentVersion\Authentication\PLAP Providers\{60442b50-aac2-4db7-b9b0-813d2107287d}"
- (Windows Vista only) HKEY_CLASSES_ROOT "CLSID\{60442b50-aac2-4db7-b9b0-813d2107287d}"

Log file Location

You can enable or disable client-side logs by clicking **System > Log/Monitoring > Client Logs > Settings** in the Web console.

When you enable logging, Network Connect adds log files to the following location:

For Windows 2000/XP:

C:\Documents and Settings\user\Application Data\Juniper Networks\Network Connect <version number>\debug.log

For Windows Vista:

C:\Users\username\AppData\roaming\Juniper Networks\logging\debuglog.log and
C:\Users\public\Juniper Networks\logging\debuglog.log

Linux Clients

The following information applies to Linux clients only.

Application and Additional Files Installed by Network Connect

Network Connect installs the following files on the Linux client:

- ~/.juniper_networks/ncLinuxApp.jar
- ~/.juniper_networks/network_connect/installNC.sh
- ~/.juniper_networks/network_connect/libncui.so
- ~/.juniper_networks/network_connect/missing.info
- ~/.juniper_networks/network_connect/ncdiag
- ~/.juniper_networks/network_connect/NC.jar
- ~/.juniper_networks/network_connect/ncsvc
- ~/.juniper_networks/network_connect/version.txt
- ~/.juniper_networks/network_connect/xlaunchNC.sh

Files Remaining After Uninstall

No files remain on the Linux client after uninstall, but the
~/.juniper_networks/network_connect/ directory does remain.

Log Files Installed by Network Connect

Network Connect installs the following log files on Linux systems:

- ~/.juniper_networks/network_connect/installnc.log
- ~/.juniper_networks/network_connect/ncsvc.log
- ~/.juniper_networks/network_connect/ncuijava.log
- ~/.juniper_networks/network_connect/ncui.log

Macintosh Clients

The following information applies to Macintosh clients only.

Application and Additional Files Installed by Network Connect

Network Connect installs the following files on the Macintosh client:

- /Applications/Network Connect.app
- /usr/local/juniper/nc/<IVE_version>/ncproxyd
- /usr/local/juniper/nc/<IVE_version>/nctun[_tiger].kext
- ~/Library/Application Support/Juniper Networks/
 - NetworkConnectMac_de.jar
 - NetworkConnectMac_en.jar
 - NetworkConnectMac_es.jar
 - NetworkConnectMac_fr.jar
 - NetworkConnectMac_ja.jar
 - NetworkConnectMac_ko.jar
 - NetworkConnectMac_zh.jar
 - NetworkConnectMac_zh-cn.jar
- ~/Library/Application Support/Juniper Networks/
 - NetworkConnectMac_ppc.jar (PowerPC-based Macintoshes)
 - NetworkConnectMac_i386.jar (Intel-based Macintoshes)
- ~/Library/Java/Extensions/libJNPRAuthKit.jnilib
- /usr/local/juniper/nc/install/NCJarVerify.jar
- /usr/local/juniper/nc/install/installer.common
- /usr/local/juniper/nc/install/ncinstallhelper
- /usr/local/juniper/nc/install/fwk_reference_tool
- /usr/local/juniper/nc/install/uninstall_nc.sh
- /usr/local/juniper/nc/install/version

Files Remaining After Uninstall

The following files remain on the Macintosh client after uninstall:

- All files in ~/Library/Logs/Juniper Networks/Network Connect
- /usr/local/juniper/nc/install/NCJarVerify.jar

- /usr/local/juniper/nc/install/installer.common
- /usr/local/juniper/nc/install/ncinstallhelper
- /usr/local/juniper/nc/install/fwk_reference_tool
- /usr/local/juniper/nc/install/uninstall_nc.sh

Log Files Installed by Network Connect

Network Connect stores the log files in the following location on the Macintosh client: ~/Library/Logs/Juniper Networks/Network Connect.

Juniper Terminal Services Client

To run Juniper Terminal Services Client, the IVE downloads the Neotermsetup.exe file (or the NeotermsetupNT.exe file for Windows 2000 and earlier) to the user's client. This package is responsible for downloading additional files to the user's system in order to execute Terminal Services.

Installer Package Files and File Locations

The IVE downloads Neotermsetup.exe (or NeotermsetupNT.exe for Windows 2000 and earlier) to the user's %Temp% directory and deletes it once the installation is complete.

Additional Files Installed by Package and File Locations

The Juniper Terminal Services Client installs additional Juniper proxy files in %APPDATA%\Juniper Networks\Juniper Terminal Services Client on the client:

The Juniper Terminal Services Client installs the following Juniper proxy files on the client:

- dsTermServ.exe
- dsTermServDt.dll
- dsTermServProxy.dll
- dsTermServResource_DE.dll
- dsTermServResource_en.dll
- dsTermServResource_ES.dll
- dsTermServResource_FR.dll
- dsTermServResource_JA.dll
- dsTermServResource_KO.dll
- dsTermServResource_ZH.dll
- dsTermServResource_ZH_CN.dll
- dsWinClient.dll

- dsWinClientResource_DE.dll
- dsWinClientResource_EN.dll
- dsWinClientResource_ES.dll
- dsWinClientResource_FR.dll
- dsWinClientResource_JA.dll
- dsWinClientResource_KO.dll
- dsWinClientResource_ZH.dll
- dsWinClientResource_ZH_CN.dll
- uninstall.exe
- versionInfo.ini

The Juniper Terminal Services Client installs the following files in %APPDATA%\Juniper Networks\Juniper Terminal Services Client\Microsoft.VC80.CRT:

- Microsoft.VC80.CRT.manifest
- msvcp80.dll
- msucr80.dll

Files Remaining After Uninstall

None

Registry Modifications

The Juniper Terminal Services Client adds the following registry values under the registry key, HKEY_CURRENT_USER\Software\Juniper Networks\Juniper Terminal Services Client.

Type	Name	Value
REG_SZ	InstallPath	%APPDATA%\Juniper Networks\Juniper Terminal Services Client
REG_SZ	Language	<user locale>. The default is en.

Juniper Terminal Services Client sets the following string registry values in HKEY_CURRENT_USER\Software\Microsoft\Windows\CurrentVersion\Uninstall\Juniper_Term_Services.

Type	Name	Value
String	DisplayName	“Juniper Terminal Services Client”
String	DisplayVersion	Set to the current software version
String	Publisher	“Juniper Networks”

Type	Name	Value
String	QuietUninstallString	"%APPDATA%\Juniper Networks\Juniper Terminal Services Client\uninstall.exe" /S
String	StartupApp	"%APPDATA%\Juniper Networks\Juniper Terminal Services Client\dsTermServ.exe"
String	StopApp	"%APPDATA%\Juniper Networks\Juniper Terminal Services Client\dsTermServ.exe" – stop
String	UninstallString	"%APPDATA%\Juniper Networks\Juniper Terminal Services Client\uninstall.exe"
String	URLInfoAbout	http://www.juniper.net

Log File Location

You can enable or disable client-side logs by clicking **System > Log/Monitoring > Client Logs > Settings** in the Web console.

When you enable logging, the Juniper Terminal Services Client adds the debuglog.log file to the following locations:

For Windows 2000/XP: %ALLUSERSPROFILE%\Application Data\Juniper Networks\Juniper Terminal Services Client

For Windows Vista: %APPDATA%\Juniper Networks\Juniper Terminal Services Client

Juniper Citrix Services Client

To execute the Juniper Citrix Services Client, the IVE downloads neoCitrixServSetup.exe to the user's client. This executable downloads additional files to the user's system.

Installer Package Files and File Locations

The IVE downloads Neocitrixsrvsetup.exe to the user's %Temp% directory and deletes it once the installation is complete.

Additional Files Installed by Package and File Locations

The Juniper Citrix Services Client installs the following Juniper proxy files on the client in %APPDATA%\Juniper Networks\Juniper Citrix Services Client.

For administrators, Citrix client files are also installed to %ProgramFiles%\Citrix where %ProgramFiles% =%SystemDrive%\Program Files.

- dsCitrixConnector.dll
- dsCitrixProxy.exe
- dsCitrixProxyResource_DE.dll
- dsCitrixProxyResource_en.dll

- dsCitrixProxyResource_ES.dll
- dsCitrixProxyResource_FR.dll
- dsCitrixProxyResource_JA.dll
- dsCitrixProxyResource_KO.dll
- dsCitrixProxyResource_ZH.dll
- dsCitrixProxyResource_ZH_CN.dll
- dsWinClient.dll
- dsWinClientResource_DE.dll
- dsWinClientResource_EN.dll
- dsWinClientResource_ES.dll
- dsWinClientResource_FR.dll
- dsWinClientResource_JA.dll
- dsWinClientResource_KO.dll
- dsWinClientResource_ZH.dll
- dsWinClientResource_ZH_CN.dll
- uninstall.exe
- versionInfo.ini

Juniper Citrix Services Client also installs the following files in %APPDATA%\Juniper Networks\Juniper Citrix Services Client\Microsoft.VC80.CRT:

- Microsoft.VC80.CRT.manifest
- msvcp80.dll
- msucr80.dll

Files Remaining After Uninstall

None

Registry Modifications

The Juniper Citrix Services client adds the following registry value under HKEY_CURRENT_USER\Software\Juniper Networks\Juniper Citrix Services Client

Type	Name	Value
REG_SZ	Language	<user locale>. The default is en.

The Juniper Citrix Services Client also sets the following registry values in HKEY_CURRENT_USER\Software\Microsoft\Windows\CurrentVersion\Uninstall\Juniper_Citrix_Services:

Type	Name	Value
String	DisplayName	"Juniper Citrix Services Client"
String	DisplayVersion	Set to the current software version
String	Publisher	"Juniper Networks"
String	QuietUninstallString	"%APPDATA%\Juniper Networks\Juniper Citrix Services Client\uninstall.exe" /S
String	StartupApp	"%APPDATA%\Juniper Networks\Juniper Citrix Services Client\dsCitrixProxy.exe"
String	StopApp	"%APPDATA%\Juniper Networks\Juniper Citrix Services Client\dsCitrixProxy.exe" – stop
String	UninstallString	"%APPDATA%\Juniper Networks\Juniper Citrix Services Client\uninstall.exe"
String	URLInfoAbout	http://www.juniper.net

Log File Location

You can enable or disable client-side logs by clicking **System > Log/Monitoring > Client Logs > Settings** in the Web console. When you enable logging, the Juniper Citrix Services Client adds the dsCitrixServ.log file to the following location:

For Windows 2000/XP: \Documents and Settings\username\Application Data\Juniper Networks\Juniper Citrix Services Client

For Windows Vista: \Users\username\AppData\Roaming\Juniper Networks\Juniper Citrix Services Client

Required rights to run and install applications

The following tables outline the rights that are required to install and run the following IVE client-side components using the IVE's ActiveX, ActiveX installer service, and Java mechanisms:

- "Windows Secure Application Manager (WSAM)" on page 32
- "Java Secure Application Manager (JSAM)" on page 32
- "Network Connect" on page 33
- "Terminal Services Component" on page 33
- "Citrix Terminal Services Component" on page 33
- "Host Checker (includes Secure Virtual Workspace)" on page 33

- “Cache Cleaner” on page 34
- “Secure Meeting” on page 34

Where applicable, the tables contain links to topics that describe in further detail the components that the IVE uses to install and run its client-side applications.

Table 1: Windows Secure Application Manager (WSAM)

	ActiveX	ActiveX: Installer Service	Java	Java	
Client/Action	Windows	Windows	Windows	Mac/Linux	More Information
Install	Admin	Restricted, Power User, or Admin	Admin	Not Applicable	See “Windows Secure Application Manager (WSAM)” on page 14
Run	Power User or Admin	Restricted, Power User, or Admin	Restricted, Power User, or Admin	Not Applicable	See “Windows Secure Application Manager (WSAM)” on page 14

Notes:

- Restricted users can perform the initial installation of WSAM with the installer service only if they start the installation by clicking the WSAM link in the user’s portal page.
- The ActiveX installer requires users to reboot their systems after an installation or upgrade.
- Users must have ActiveX components or Java enabled through their browsers to use the WSAM installers.

Table 2: Java Secure Application Manager (JSAM)

	ActiveX	ActiveX: Installer Service	Java	Java	
Client/Action	Windows	Windows	Windows	Mac/Linux	More Information
JSAM					
Run	Not Applicable	Not Applicable	Restricted, Power User, or Admin	User	See “Java Secure Application Manager (JSAM)” on page 20
JSAM with Host File Modification					
Run	Not Applicable	Not Applicable	Admin	Admin/Root	See “Java Secure Application Manager (JSAM)” on page 20

Notes

Client system asks for the administrator password when JSAM launches.

Table 3: Network Connect

	ActiveX	ActiveX: Installer Service	Java	Java	
Action	Windows	Windows	Windows	Mac/Linux	More Information
Install	Admin	Restricted, Power User, or Admin	Admin	Admin ^a	See “Network Connect and GINA” on page 22
Run	Power User or Admin	Restricted, Power User, or Admin	Power User or Admin	Standard User	See “Network Connect and GINA” on page 22

a. Linux also requires Admin rights to upgrade or downgrade Network Connect. Macintosh does not have this restriction.

Table 4: Terminal Services Component

	ActiveX	ActiveX: Installer Service	Java	Java	
Action	Windows	Windows	Windows	Mac/Linux	More Information
Install	Power User or Admin	Restricted, Power User, or Admin	Restricted, Power User, or Admin	Not Applicable	See “Juniper Terminal Services Client” on page 27
Run	Restricted, Power User, or Admin	Restricted, Power User, or Admin	Restricted, Power User, or Admin	Not Applicable	See “Juniper Terminal Services Client” on page 27

Table 5: Citrix Terminal Services Component

	ActiveX	ActiveX: Installer Service	Java	Java		
Action	Windows	Windows	Windows	Mac/Linux	Citrix Client	More Information
Install	Power User or Admin	Restricted, Power User, or Admin	Restricted, Power User, or Admin	Not Applicable	Power User or Admin	See “Juniper Terminal Services Client” on page 27
Run	Restricted, Power User, or Admin	Restricted, Power User, or Admin	Restricted, Power User, or Admin	Not Applicable	Restricted, Power User, or Admin	See “Juniper Terminal Services Client” on page 27

Table 6: Host Checker (includes Secure Virtual Workspace)

	ActiveX	ActiveX: Installer Service	Java	Java	
Action	Windows	Windows	Windows	Mac/Linux	More Information
Install	Restricted, Power User, or Admin	Restricted, Power User, or Admin	Restricted, Power User, or Admin	Not Applicable	See “Host Checker” on page 6

Table 6: Host Checker (includes Secure Virtual Workspace)(Continued)

	ActiveX	ActiveX: Installer Service	Java	Java	
Action	Windows	Windows	Windows	Mac/Linux	More Information
Run	Restricted, Power User, or Admin	Restricted, Power User, or Admin	Restricted, Power User, or Admin	Not Applicable	See “Host Checker” on page 6

NOTE: If you implement SVW through Host Checker, note that restricted users, power users, and admins all have adequate rights to install and run SVW.



NOTE: If you enable the **Advanced Endpoint Defense Malware Detection** Host Checker option and enforce the policy to install the Whole Security Confidence Online software on users’ computers, be aware of the following:

- **Category 1 and Category 2 Signature Scans**—Restricted users, power users, and administrators can install and run the scanning feature in Confidence Online. The scanning feature is supported on Windows NT4, Windows 2000, and Windows XP systems.
- **Behavior Blocker**—Only administrators can install and run the behavior blocker feature in Confidence Online. The behavior blocker feature is supported on Windows 2000 and Windows XP systems.

Table 7: Cache Cleaner

	ActiveX	ActiveX: Installer Service	Java	Java	
Action	Windows	Windows	Windows	Mac/Linux	More Information
Install	Restricted, Power User, or Admin	Restricted, Power User, or Admin	Restricted, Power User, or Admin	Not Applicable	See “Cache Cleaner” on page 10
Run	Restricted, Power User, or Admin	Restricted, Power User, or Admin	Restricted, Power User, or Admin	Not Applicable	See “Cache Cleaner” on page 10

Table 8: Secure Meeting

	ActiveX	ActiveX: Installer Service	Java	Java	
Action	Windows	Windows	Windows	Mac/Linux	More Information
Secure Meeting: Win32					
Install	Restricted, Power User, or Admin	Not Applicable	Restricted, Power User, or Admin	Not Applicable	See “Secure Meeting” on page 11

Table 8: Secure Meeting (Continued)

	ActiveX	ActiveX: Installer Service	Java	Java	
Action	Windows	Windows	Windows	Mac/Linux	More Information
Run	Restricted, Power User, or Admin	Not Applicable	Restricted, Power User, or Admin	Not Applicable	See “Secure Meeting” on page 11
Secure Meeting: Java					
Install	Restricted, Power User, or Admin	Not Applicable	Restricted, Power User, or Admin	User	See “Secure Meeting” on page 11
Run	Restricted, Power User, or Admin	Not Applicable	Restricted, Power User, or Admin	User	See “Secure Meeting” on page 11
Secure Meeting: Outlook Plug-in					
Install	Restricted, Power User, or Admin	Not Applicable	Restricted, Power User, or Admin	Not Applicable	See “Secure Meeting” on page 11
Run	Restricted, Power User, or Admin	Not Applicable	Restricted, Power User, or Admin	Not Applicable	See “Secure Meeting” on page 11

